



Combined System: Non pressurised Rainwater, Blue Roof & Active Attenuation

The UK Market Leaders For Water Reuse

T: 01636 815 254

www.stormsaver.com

Stormsaver Combined system: Non Pressurised Rainwater, Blue Roof & Active Attenuation

1. Blue roof rainwater collection and storage
2. Rainwater enters drainage through flow restrictor
3. High-level rainwater diverter valve
4. Active attenuation diverter valve
5. Rainwater passes through pre-tank filter
6. Inlet calmer
7. Mains cold water supply (top up)
8. Overflow from rainwater storage tank with NRV
9. Sump pit and submersible pump
10. Storm drain manhole
11. Rainwater external booster set
12. Stormsaver Standard control panel
13. Optional BMS (by others)
14. Local power supply
15. Optional micron filtration
16. Optional UV disinfection unit
17. Active attenuation control panel
18. Active attenuation external gsm antenna
19. Optional monitoring unit
20. Points of use

Disclaimer

This schematic is to be used as a general overview of a typical Stormsaver Water Reuse System layout. It is not site specific and should not be relied upon for technical submittal or installation guidance.



Water Reuse Specialists

T: 01636 815 254

W: www.stormsaver.com

The system design rights and copyright remains the property of Stormsaver Ltd. Contact us on 01636 815 254 for more details www.stormsaver.com

